

阻燃PP薄膜
FR PP FILM

QEHS/LHJS-PRMA-013-2013-01

龍華®
Longhua

LonghuaPP-xx/WT 20/BK20 FILM

产品描述 Description:

Longhua PP-xx/WT 20/BK20阻燃级聚丙烯薄膜，UL94防火等级达到V-0 & VTM-0，此产品不含有六溴环十二烷，符合欧盟ROHS指令及严格的UL安全规范。可以广泛用于电源供应器、电视/显示器、商务机等折合和贴合绝缘及遮蔽。

LonghuaPP-xx/WT 20/ BK20 are flame-retardant polypropylene films/sheets. Meet to ROHS directive free of PBCD contents and UL94 V-0 & VTM-0 listed. They are widely used in power supply, TV/monitors, business equipments and foil laminated for insulation and shielding purposes.

UL File Number: E254551

商品代码 Grades	颜色 Color	表面纹理 Textures	厚度(mm) Thicknesses	宽度(mm) Widths	行业型号对照 VS Other Brands
LonghuaPP-WT20	白色 White	哑光/中砂 Matte/Velvet	0.125 ~ 0.25 (0.005" ~ 0.010")	610 (2')	GK-10
LonghuaPP-WT17		半哑光/中砂 Fine matte/Velvet	0.400 ~ 1.500 (0.016" ~ 0.060")		GK-17 ~ GK-40
LonghuaPP-BK20	黑色 Black	哑光/中砂 Matte/Velvet	0.125 ~ 0.250 (0.005" ~ 0.010")		GK-5BK、GK-10
LonghuaPP-BK18		半哑光/中砂 Fine matte/Velvet	0.400 ~ 1.500 (0.016" ~ 0.060")		GK-17 ~ GK-62

包装明细表Package Details

1. 卷材包装明细表 Roll Package Details

厚度(mm) Thicknesses	卷重(kg) Weight Per Roll	磅重 (LB) Pounds	每磅面积(mm) Each Pound Area 宽(W) × 长(L)	每卷卷长(m) Winding Length	每磅面积(M ² /LB) Each Pound Area
0.125 (0.005")	80	176	610 × 5961	1049	3.64
0.25 (0.010")	80	176	610 × 2984	524	1.82
0.43 (0.017")	80	176	610 × 1738	305	1.06
0.45 (0.018")	80	176	610 × 1655	291	1.01
0.76 (0.030")	80	176	610 × 967	172	0.59

2. 片材包装明细表 Sheets Package Details

规格 Size	每片重量Weight per pcs		包装 Pcs/pack	张数/托盘 Pcs/Pallet
	kg	LB		
0.760mm × 610mm × 930mm (0.030" × 2' × 3')	0.43	0.95	30	900
0.760mm × 610mm × 1230mm (0.030" × 2' × 4')	0.57	1.26	30	900
1.00mm × 610mm × 930mm (0.040" × 2' × 3')	0.57	1.26	30	900
1.00mm × 610mm × 1230mm (0.040" × 2' × 4')	0.75	1.65	30	900

特性 PROPERTIES	单位 UNITS	极限值 LIMITS
厚度公差 Gauge Variation	mm	0.125 ~ 0.380mm ± 0.02mm 0.430 ~ 0.450mm +0.04mm/-0.03mm 0.760 ~ 1.000mm ± 0.05mm 1.5mm ± 0.1mm